



Serie 100.45L



- Art.nummers -

80	30	40,5	12		150	100.456.800B
80	30	40,5	15		150	100.456.800C
100	35	44	12		250	100.456.100B
100	35	44	15		250	100.456.100C
100	40	45	12		325	100.457.100B
100	40	45	15		325	100.457.100C
100	40	45	20		325	100.457.100E
100	65	65	20		575	100.456.102E
100	65	65	25		575	100.456.102F
100	65	65	30		575	100.456.102G
125	35	44	12		325	100.456.120B
125	35	44	15		325	100.456.120C
125	40	60	20		400	100.456.122E
125	65	65	20		675	100.457.122E
125	65	65	25		675	100.457.122F
125	65	65	30		675	100.457.122G
150	40	60	20		450	100.456.150E
150	40	60	25		450	100.456.150F
150	65	65	20		700	100.456.152E
150	65	65	25		700	100.456.152F
150	65	65	30		700	100.456.152G
160	50	50	20		550	100.456.161E
160	50	50	25		550	100.456.161F
160	50	60	20		550	100.456.160E
160	50	60	25		550	100.456.160F
180	65	65	25		900	100.456.182F
180	65	65	30		900	100.456.182G
200	50	50	20		800	100.456.201E
200	50	50	25		800	100.456.201F
200	50	50	30		800	100.456.201G

LOSSE WIELEN

- vulkollan band

150-3200 kg



						– Art.nummers –
200	50	60	20		800	100.456.200E
200	50	60	25		800	100.456.200F
200	50	60	30		800	100.456.200G
200	65	65	25		1100	100.458.200F
200	65	65	30		1100	100.458.200G
200	65	65	35		1100	100.458.200H
200	80	80	40		1300	100.456.202I
250	50	50	20		900	100.456.251E
250	50	50	25		900	100.456.251F
250	50	50	30		900	100.456.251G
250	50	60	20		900	100.457.251E
250	50	60	25		900	100.457.251F
250	50	60	30		900	100.457.251G
250	65	65	25		1000	100.456.250F
250	65	65	30		1000	100.456.250G
250	65	65	35		1000	100.456.250H
300	50	60	25		1000	100.458.301F
300	50	60	30		1000	100.458.301G
300	50	60	35		1000	100.458.301H
300	65	65	25		1250	100.456.301F
300	65	65	30		1250	100.456.301G
300	65	65	35		1250	100.456.301H
300	80	80	30		2000	100.456.300G
300	80	80	35		2000	100.456.300H
300	80	80	40		2000	100.456.300I
300	100	100	30		2400	100.456.302G
300	100	100	35		2400	100.456.302H
300	100	100	40		2400	100.456.302I
350	80	80	30		2250	100.456.350G
350	80	80	35		2250	100.456.350H
350	80	80	40		2250	100.456.350I
350	80	80	45		2250	100.456.350K
350	100	100	35		2600	100.456.352H
350	100	100	40		2600	100.456.352I
350	100	100	45		2600	100.456.352K
360	65	65	25		1500	100.456.360F
360	65	65	30		1500	100.456.360G
360	65	65	35		1500	100.456.360H
400	65	65	25		1700	100.456.401F
400	65	65	30		1700	100.456.401G
400	65	65	35		1700	100.456.401H



– Art.nummers –

400	80	80	30		2400	100.456.400G
400	80	80	35		2400	100.456.400H
400	80	80	40		2400	100.456.400I
400	80	80	45		2400	100.456.400K
400	100	100	40		3200	100.457.402I
400	100	100	45		3200	100.457.402K
400	100	100	50		3200	100.457.402L
450	80	80	40		2700	100.456.451I
450	80	80	45		2700	100.456.451K
450	80	80	50		2700	100.456.451L
500	80	80	40		3000	100.456.501I
500	80	80	45		3000	100.456.501K
500	80	80	50		3000	100.456.501L

Omschrijving

Wielen:

serie 45L - gietijzeren velg, met opgevulkaniseerde vulkollan band, kogellager.

Uitvoering L: dikkere band, meer rijcomfort.

Ook leverbaar:

- tot Ø 750 mm.
- afwijkende asgat- en wielafmetingen.
- aandrijf wiel met spiebaan.

****Uitvoering wiel kan afwijken van getoonde foto!!**



Serie 100.45B



– Art.nummers –

100	50	50	20		400	100.457.102E
100	50	50	25		400	100.457.102F
125	40	45	15		400	100.457.120C
125	40	45	20		400	100.457.120E
125	50	50	20		500	100.458.122E
125	50	50	25		500	100.458.122F
150	50	50	20		550	100.457.150E
150	50	50	25		550	100.457.150F
180	80	80	25		900	100.457.182F
200	50	60	20		900	100.457.200E
200	50	60	25		900	100.457.200F
200	50	60	30		900	100.457.200G
200	80	80	20		1400	100.457.202E
200	80	80	25		1400	100.457.202F
200	80	80	30		1400	100.457.202G
200	80	80	35		1400	100.457.202H
250	50	60	20		950	100.458.251E
250	50	60	25		950	100.458.251F
250	50	60	30		950	100.458.251G
250	80	80	30		1700	100.457.252G
250	80	80	35		1700	100.457.252H
250	80	80	40		1700	100.457.252I

Omschrijving

Wielen:

serie 45B - gietijzeren velg met Vulkollan band en kogellager.

uitvoering B: dunne band, lage rolweerstand.

Ook leverbaar:

- afwijkend asgat.
- afwijkende afmetingen.
- spiebaan.



Serie 100.45



250	130	130	30		2500	100.458.252G
250	130	130	35		2500	100.458.252H
300	135	135	50		3000	100.458.302L
300	135	135	60		3000	100.458.302N
400	125	125	40		3700	100.458.402I
400	125	125	45		3700	100.458.402K
400	125	125	50		3700	100.458.402L
400	125	125	55		3700	100.458.402M
400	125	125	60		3700	100.458.402N
400	125	125	65		3700	100.458.402P
425	150	150	40		4050	100.456.420I
425	150	150	60		4050	100.456.420N
450	100	100	40		3400	100.456.450I
450	100	100	45		3400	100.456.450K
450	100	100	50		3400	100.456.450L
450	100	100	55		3400	100.456.450M
450	100	100	60		3400	100.456.450N
450	125	125	40		3850	100.456.452I
450	125	125	45		3850	100.456.452K
450	125	125	50		3850	100.456.452L
450	125	125	55		3850	100.456.452M
450	125	125	60		3850	100.456.452N
500	100	100	40		3750	100.456.500I
500	100	100	45		3750	100.456.500K
500	100	100	50		3750	100.456.500L
500	100	100	55		3750	100.456.500M
500	100	100	60		3750	100.456.500N
500	125	125	50		4250	100.456.502L
500	125	125	55		4250	100.456.502M
500	125	125	60		4250	100.456.502N



						– Art.nummers –
500	125	125	65		4250	100.456.502P
500	125	125	70		4250	100.456.502R
500	150	150	50		5100	100.457.502L
500	150	150	55		5100	100.457.502M
500	150	150	60		5100	100.457.502N
500	150	150	65		5100	100.457.502P
500	150	150	70		5100	100.457.502R
500	230	230	70		7250	100.458.502R
530	150	150	50		5250	100.456.530L
530	150	150	55		5250	100.456.530M
530	150	150	60		5250	100.456.530N
530	150	150	65		5250	100.456.530P
530	150	150	70		5250	100.456.530R
600	150	150	55		5650	100.456.600M
600	150	150	60		5650	100.456.600N
600	150	150	65		5650	100.456.600P
600	150	150	70		5650	100.456.600R
600	150	150	75		5650	100.456.600S
600	150	150	80		5650	100.456.600T
600	175	175	60		6600	100.456.602N
600	175	175	65		6600	100.456.602P
600	175	175	70		6600	100.456.602R
600	175	175	75		6600	100.456.602S
600	175	175	80		6600	100.456.602T
600	175	175	85		6600	100.456.602U
600	175	175	90		6600	100.456.602V

Omschrijving

Vulkollan Wielen:

serie 45 - staalgelaste velg met Vulkollan band 90° of 95 ° shore A, kogellager.

Ook leverbaar:

- afwijkend asgat
- afwijkende afmetingen
- spiebaan
- flensaansluiting

*Uitvoering wiel kan afwijken van getoonde foto